

R4000 COMPACT SII EDGE BANDER

- Heavy Duty Construction, heat treated prior to machining
- Tape thickness:0.4-2mm
- Work piece thickness: 12-45mm
- Min. work piece width:80mm
- Min. work piece length: 150mm
- Feeding speed: 12mt/min.
- Motorised caterpillar track with top pressure rollers
- Insulated sound proof hood with large viewing window & fluorescent lighting
- Top beam with rise/fall electrically set
- 6 Wing large diameter radius cutters
- Top & Bottom Edge Trimming
- Top & Bottom Radius Scrapers
- Top & Bottom Buffing
- Temperature stand by if not used for a pre-determined period of time
- Teflon coated hot melt glue pot
- Safety distance infeed stop cylinder
- Pre-heated infeed fence
- End cutting by 2 x 0.5kW 12,000rpm
- Edge trimming by 2 x 0.5kW 12,000rpm
- All high frequency motors fitted with 3 Phase DELTA inverters for more power & braking
- DELTA Touch Screen for all controls
- Runs on 20Amp 3 Phase electric circuit
- Dust extraction electrics for upto 4kW dust unit built in & starts up with feed track
- One common 150mm dia. Dust extraction outlet via manifold
- Digital readouts on trimmers & scrapers
- Dust extraction on trimmers, scrapers & under cut off saws
- Packing size 2750 x 750 x 1600mm (h)

