

R4000 RC (Rapid Change) Fully Featured Edge Bander

- Heavy Duty Construction, heat treated prior to machining
- Tape width: 15-58mm
- Tape thickness: 0.4-2mm
- Work piece thickness: 12-55mm
- Min. work piece width: 80mm
- Min. work piece length: 120mm
- Feeding speed: 12-20mt/min.
- Dual tape holder
- Teflon coated glue pot
- Temperature stand by if not used for a pre-determined period of time
- 15 - 20 minute heat up time of glue pot
- Safety distance infeed cylinder
- Italian end cutting motors 2 x 0.5kW 12,000rpm
- Linear guide rail for end cutting function
- End cutting unit with adjustable angle
- Italian fine trimming motors 2 x 0.5kW 12,000rpm
- Fine trimming unit adjustable 0-45 degrees
- All Italian high frequency motors fitted with DELTA 3 phase inverters for more power & braking
- DELTA Touch Screen for all controls
- Rapid change from 1-2mm with one touch on the screen
- Linear bearings on horizontal guides
- Electric rise & fall of top beam with digital display for panel thickness
- Dust extraction on scrapers & trimmers
- Sound proofing of hood with large viewing window incorporating cabin lighting
- Runs on 20Amp 3 Phase electric circuit
- Dust extraction electrics & controls for upto 4kW dust unit built in & starts up with feed track
- Packing size 4600 x 1000 x 1700mm (h)
Weight 1200kg

